



Paint Manufacturers

3 Pendrey Court, Woodridge, Qld 4114
 Phone : (07) 3290 1444 Fax : (07) 3290 1555

Issued 15th March 2005

PRODUCT DATA SHEET

111 SILICONE 18

Description	Silicone 18 is an excellent, long lasting water repellent for the treatment of above ground masonry. Especially suitable for concrete, masonry and render walls.	
Features	<ul style="list-style-type: none"> • Does not alter natural look • Does not support fungus • Decreases ability of water to penetrate • Dirt remains on surface • Reduces efflorescence 	
Typical Uses	Efficient, economical protection for buildings, bridges, towers, silos, reservoirs, monuments, fibrous cement sheet roofs and walls. Keeps concrete block, fibrous or asbestos cement sheeting, concrete, artificial masonry block, clay brick, stone, cinder block, unglazed tile etc. dry and clean.	
Application Data	Gloss:	N/A
	Colour:	N/A
	Shelf Life @ 25°C:	12-24 months
	Thinning:	N/A
	Clean Up:	White Spirits
	Spread Rate:	0.5-1m ² /lt less losses due to application method, conditions of application and surface characteristics
	Dry Times:	Dry by absorption: 12 hours
	Application:	May be applied by conventional spray, flooding or rolling. To achieve maximum build do not thin.
	Container Sizes:	4 litre, 20 litre, 200 litre
Application Summary¹	Surface preparation of both new and old masonry walls is important: - <ol style="list-style-type: none"> a) repair all cracks and rejoin faulty joints. Silicone 18 will not waterproof holes or open cracks larger than hairline cracks. b) Remove dirt, moss, algae, fungus, loose particles, paint and any other contaminants. 	

- c) Silicone 18 should only be applied on dry days. Avoid treating surfaces which are noticeably damp and ensure that treated surfaces will be free of water for at least 6 hours.

Precautions Contains flammable solvents. Keep away from heat and flame. Provide adequate ventilation and wear protective clothing. Material Safety Data Sheet available on request.

Classification UN 1263
 DG CLASS 3 PKG II
 HAZCHEM 3 [Y]E

¹ For more comprehensive preparation information please read Paintec's Guidelines for Preparation and Protection of Concrete Surfaces.

Paintec Pty Ltd
3 Pendrey Court
Woodridge Qld 4114

Phone (07) 3290-1444
Fax (07) 3290-1555

Due to differences in substrates, application methods and local conditions purchasers of this product must ensure that it is suitable for their specific application before using this product. While the information contained in the PDS is accurate to the best of our knowledge, Paintec Pty Ltd cannot guarantee that the information contained is wholly comprehensive. Subject to the provisions of the Trade Practices Act, the Company's liability in relation to defective product shall be limited to replacement or repair of the product or the supply of equivalent product.