



Paint Manufacturers

3 Pendrey Court, Woodridge, Qld 4114
 Phone : (07) 3290 1444 Fax : (07) 3290 1555

Issued 1st August 2005

PRODUCT DATA SHEET

120 WOODPRIME

Description Woodprime is an oil-based primer for timber surfaces that displays excellent filling and sanding properties, as well as excellent adhesion over both new and previously painted surfaces.

Features

- Ease of sanding
-
-

Typical Uses Recommended as a primer for such surfaces as timber doors, outdoor furniture, timber railings, and window frames.

Application Data

Gloss:	N/A
Colour:	White, Off White, Pink, Buff
Shelf Life @ 25°C:	6-12 months
Thinner:	Enamel Thinner or Mineral Turps
Clean Up:	Mineral Turps
Volume Solids:	
Spread Rate:	10-12 m ² /lt (micron DFT) less losses due to application method, conditions of application and surface characteristics
Dry Times:	Dust Free: Touch Dry: Hard Dry: 2 hours
Application:	May be applied by brush, roller or spray. To achieve maximum build do not thin, but it may be necessary to thin up to 10% with Enamel thinner when spraying or Mineral Turps when brushing/rolling depending on application equipment used.
Container Sizes:	4 litre, 20 litre

Application Summary Prepare surface by filling imperfections with timber putty. Sand smooth with 180-240 grade fre-cut paper and remove sanding dust. Ensure that you sand in the direction of the grain.

Stir contents thoroughly before applying by brush, roller or spray. Leave 24 hours before recoating. Before applying topcoat, it is recommended to lightly sand with 280-320 fre-cut paper

Precautions Contains flammable solvents. Keep away from heat and flame. Provide adequate ventilation and wear protective clothing. Material Safety Data Sheet available on request.

Classification UN 1263
DG CLASS 3 PKG II
HAZCHEM 3 [Y]E

Paintec Pty Ltd
3 Pendrey Court
Woodridge Qld 4114

Phone (07) 3290-1444
Fax (07) 3290-1555

Due to differences in substrates, application methods and local conditions purchasers of this product must ensure that it is suitable for their specific application before using this product. While the information contained in the PDS is accurate to the best of our knowledge, Paintec Pty Ltd cannot guarantee that the information contained is wholly comprehensive. Subject to the provisions of the Trade Practices Act, the Company's liability in relation to defective product shall be limited to replacement or repair of the product or the supply of equivalent product.